

## CERTIFICATE OF CONFORMITY

<b>Product:</b>	Minibar
<b>Tested by request of</b>	MN Minibar Inovasyon Yatırım LTD. STI. Kayseri OSB Mah 19. Cad. No: 8 Kayseri/Turkey
<b>Manufactured at (name and place)</b>	MN Minibar Inovasyon Yatırım LTD. STI. Kayseri OSB Mah 19. Cad. No: 8 Kayseri/Turkey
<b>Trade mark (if any):</b>	MN Bar&MN Cooling
<b>Model/Type Ref:</b>	See the page 2
<b>Ratings and principal characteristics:</b>	230 V~ AC 50 Hz -70W , 0,30A
<b>Additional information (if any):</b>	see the Appendix

A sample of the product has been tested and found to be in conformity with:

IEC 60335-2-24:2020 in conjunction with IEC 60335-1:2010, IEC 60335-1:2010/COR1:2010, IEC 60335-1:2010/COR2:2010, IEC 60335-1:2010/AMD1:2013, IEC 60335-1:2010/AMD1:2013/COR1:2014, IEC 60335-1:2010/AMD2:2016, IEC 60335-1:2010/AMD2:2016/COR1:2016

EN 60335-2-24:2010 + A1:2019 + A2:2019 used in conjunction with EN 60335 1:2012 + AC:2014 + A11:2014 + A13:2017 + A1:2019 + A14:2019 + A2:2019 EN 62233:2008 + AC:2008

as shown in the test report(s) TR\_2021779\_1

This Certificate of Conformity is the result of testing a sample of the product submitted, in accordance with the provisions of the relevant specific standard. It does not imply an assessment of the whole production. This Certificate of Conformity has been issued in accordance with the SGS Supervise Gözetme Etüd Kontrol Serv. A.Ş. which is available on request. Conformity of the produced products with the specimen tested remains on the full responsibility of the manufacturer.

Turkey, 22/10/2021

Mahmut Aksakallı  
E&E Lab Team Leader



**Certificate of Conformity-Appendix**

**General product information:**

- Minibar, Class I appliance for indoor use, Supply cord with plug; Type Y

Trade Mark	Model	Gross Volume	Temperature adjustment	Rated power and frequency	Rated current	Rated power	Climatic class	Ref. Gas.	Lighting	Door Type
MN Bar MN Cooling	MNK 30NH	35 L	Mechanical Thermostat	230 V 50-60 Hz	0,30A	60 W	N	NH3 220 g	Optional led Max:2 W	Polyurethane padding
	MNK 30NH-G	35 L								Glass
	MNK 40NH	40 L								Polyurethane padding
	MNK 40NH-G	40 L				Glass				
	MNK 60NH	60 L				70 W				Polyurethane padding
	MNK 60NH-G	60 L				Glass				

