

CERTIFICATE OF CONFORMITY

Product:	Mini refrigerator
Tested by request of	MN Minibar Inovasyon Yatırım LTD. STI. Kayseri OSB Mah 19. Cad. No: 8 Kayseri/Turkey
Manufactured at (name and place)	MN Minibar Inovasyon Yatırım LTD. STI. Kayseri OSB Mah 19. Cad. No: 8 Kayseri/Turkey
Trade mark (if any):	MN Bar&MN Cooling
Model/Type Ref:	See the page 2
Ratings and principal characteristics:	220-240 V~ AC 50 Hz -68W
Additional information (if any):	see the Appendix

A sample of the product has been tested and found to be in conformity with:

IEC 60335-2-24:2020 in conjunction with IEC 60335-1:2010, IEC 60335-1:2010/COR1:2010, IEC 60335-1:2010/COR2:2010, IEC 60335-1:2010/AMD1:2013, IEC 60335-1:2010/AMD1:2013/COR1:2014, IEC 60335-1:2010/AMD2:2016, IEC 60335-1:2010/AMD2:2016/COR1:2016

EN 60335-2-24:2010 + A1:2019 + A2:2019 used in conjunction with EN 60335 1:2012 + AC:2014 + A11:2014 + A13:2017 + A1:2019 + A14:2019 + A2:2019 EN 62233:2008 + AC:2008

as shown in the test report(s) TR_2021924_1

This Certificate of Conformity is the result of testing a sample of the product submitted, in accordance with the provisions of the relevant specific standard. It does not imply an assessment of the whole production. This Certificate of Conformity has been issued in accordance with the SGS Supervise Gözetme Etüd Kontrol Serv. A.Ş. which is available on request. Conformity of the produced products with the specimen tested remains on the full responsibility of the manufacturer.

Turkey, 22/10/2021

Mahmut Aksakallı
E&E Lab. Team Leader



Certificate of Conformity-Appendix

General product information:

- Mini refrigerator, Class I appliance for indoor use, Supply cord with plug; Type Y

Trade Mark	Model	Gross Volume	Temperature adjustment	Rated power and frequency	Rated current	Rated power	Climatic class	Ref. Gas.	Lighting	Door Type
MN Bar MN Cooling	MNK 30C	35 L	Mechanical Thermostat	230 V 50-60 Hz	0,30A	68 W	N	R600a 20 g	Optional led Max:2 W	Polyurethane padding
	MNK 30C-G	35 L								Glass
	MNK 40C	40 L								Polyurethane padding
	MNK 40C-G	40 L								Glass
	MNK 60C	60 L								Polyurethane padding
	MNK 60C-G	60 L								Glass

